

ON-450

Power by WEICHAI

WP13D440E200

Prime power: 360KW/450KVA

Standby power: 400KW/500KVA

GENERATING POWER SOLUTIONS

Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs



The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.



ONEWPOWER

WWW.ONEWPOWER.COM

DIMENSION		OPEN TYPE	SILENT TYPE
Length (L)	mm	2990	4212
Width (W)	mm	1300	1500
Height (H)	mm	1709	2236
Dry weight	kg	2700	3878
Fuel tank	L	NA	650

Technical Data

Model ON-450

Rated prime power	KW	360
Rated standard power	KW	400
Rated voltage line to line	V	380~415
Maximun sound level	dB(@7m)	≤72

Engine

Model	WP13D440E200	
Aspiration	Turbochargine and aftercooled	
Fuel system	mechanical pump	
No. cylinders	6	
Displacement	Liquid	12.54
Bore*Stroke	mm	127*165
Compression ratio	16:1	
Rated speed	r/min	1500
Rated net power(with fan)	Kw	360
Governor type	ECU	

Exhaust system

Exhaust gas flow		1964kg/h
Exhaust gas temp	° F (° C)	<740
Max back pressure		12Kpa

Aspiration system

Max inlet pressure	kPa	≤3.5
Combustion volume	L/s	/
Air flow	kg/h	1887

Fuel system

100% load(Prime power)	L/h	93
75% load(Prime power)	L/h	66.4
50% load(Prime power)	L/h	44.8
Fuel tank capacity	L	650

Lubrication system

Oil capacity	L	30
Oil consumption	L/H	93
Oil pressure	kPa	10
(continuous operation)		

Cooling system

Coolant capacity	L	25
Thermostat operation range	°C	76-88
Max water temperature	°C	98

Alternator

Model	ON-450	
Phase	3	
Voltage	V	380~415
Bearing	1	
Power factor	0.8	
Frequency	Hz	50
Prime power	KW	360
Exciter Type	Brushless, self-excitation	
Voltage regulation	%	±0.5
Protection Grade	IP 23	
Insulation grade	H/H	
Altitude	m	≤1000

Controller

- Model
- Protective functions:
- Low oil pressure
 - High water temperature
 - High/low voltage
 - High Engine Temperature and Overspeed.
 - Voltage regulator frequency regulator
 - Emergency stop
 - Start failure



Control Module Options



- Auto generator control module
- Control module with "Three Remote Control" functions
- ATS auto load transfer screen
- Synchronising control modules
- Power output cabinet

